

1. TABULAR DESCRIPTION

BITIS 2J ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	BITIS	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS484	-	017 (016.0)	+1	68.3	-	+4550	-	RNAV 1
030	TF	TS482	-	017 (016.0)	+1	23.2	-	+3650	-	RNAV 1
040	TF	BUTGA	-	049 (047.6)	+1	37.5	-	+2150	-460	RNAV 1
050	TF	NUNGO	-	095 (094.0)	+1	12.2	-	@2150	-	RNAV 1
060	TF	TS468	-	095 (094.0)	+1	12.9	-	-	-	RNAV 1
070	TF	TS466	-	109 (108.0)	+1	12.0	-	-	-	RNAV 1
080	TF	TS464	-	126 (125.0)	+1	12.0	-	-	-	RNAV 1
090	TF	TS462	-	142 (140.5)	+1	9.9	-	@2150	-	RNAV 1
100	TF	BOMSU	-	239 (237.5)	+1	40.7	-	-1500 +790	-425	RNAV 1

TRN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TRN	-	-	+1	-	-	-	-	RNAV 1
020	TF	BITIS	-	072 (071.2)	+1	62.8	-	-	-	RNAV 1

SAPEN 2J ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	SAPEN	-	-	+1	-	-	-	-	RNAV 1
020	TF	BUTGA	-	065 (063.5)	+1	67.0	-	+2150	-460	RNAV 1
030	TF	NUNGO	-	095 (094.0)	+1	12.2	-	@2150	-	RNAV 1
040	TF	TS468	-	095 (094.0)	+1	12.9	-	-	-	RNAV 1
050	TF	TS466	-	109 (108.0)	+1	12.0	-	-	-	RNAV 1
060	TF	TS464	-	126 (125.0)	+1	12.0	-	-	-	RNAV 1
070	TF	TS462	-	142 (140.5)	+1	9.9	-	@2150	-	RNAV 1
080	TF	BOMSU	-	239 (237.5)	+1	40.7	-	-1500 +790	-425	RNAV 1