

1. TABULAR DESCRIPTION

DALAP 2J ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DALAP	-	-	+1	-	-	@3350	-460	RNAV 1
020	TF	ANSUP	-	259 (258.0)	+1	17.7	-	@2750	-	RNAV 1
030	TF	TS448	-	340 (339.2)	+1	11.2	-	-	-	RNAV 1
040	TF	TS446	-	323 (322.0)	+1	10.9	-	-	-	RNAV 1
050	TF	TS444	-	306 (305.0)	+1	10.9	-	-	-	RNAV 1
060	TF	TS442	-	289 (288.0)	+1	10.9	-	@2750	-	RNAV 1
070	TF	BOMSU	-	190 (189.5)	+1	37.0	-	-1500 +790	-425	RNAV 1

RINKU TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS918	-	135 (134.2)	+1	26.5	-	-	-	RNAV 1
030	TF	TS916	-	147 (146.2)	+1	26.5	-	-	-	RNAV 1
040	TF	TS914	-	159 (158.3)	+1	26.5	-	-	-	RNAV 1
050	TF	TS912	-	171 (170.3)	+1	26.5	-	-	-	RNAV 1
060	TF	RINKU	-	183 (181.9)	+1	24.7	-	-	-	RNAV 1
070	TF	DALAP	-	278 (277.4)	+1	127.0	-	@3350	-460	RNAV 1

DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	219 (218.2)	+1	127.0	-	@3350	-460	RNAV 1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	PTH	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	278 (277.3)	+1	75.2	-	@3350	-460	RNAV 1

VETOM TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	VETOM	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	226 (224.6)	+1	34.0	-	@3350	-460	RNAV 1

ELSAS TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	ELSAS	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	351 (349.9)	+1	98.6	-	@3350	-460	RNAV 1