

APCH procedure coding of RNP Z RWY 02L

1. RNP Z APPROACH PROCEDURE RWY 02L

| RCMD.PATH TERMINATOR | FIX ID (WPT NAME) | FLY- OVER | DISTANCE (KM) | MAG TRACK (TRUE TRACK) | TURN DIRECTION | ALTITUDE (M) | SPEED LIMIT (IAS) KM/H | VER ANGLE | NAV PER |
|-------------------------|----------------------|--------------|------------------|---------------------------|-------------------|-----------------|---------------------------------|--------------|----------|
| IF | CR021 | - | - | - | - | 1500 | - | - | RNP APCH |
| TF | CR022 | - | 14.8 | 297°(295.9°) | - | +795 | - | - | RNP APCH |
| TF | CR023 | - | 6.2 | 020°(018.8°) | - | 652 | - | - | RNP APCH |
| TF | MAPT RWY 02L | Y | 7.9 | 020°(018.9°) | - | 180 | - | 6.0% | RNP APCH |
| DF | CR218 | - | - | - | - | - | - | - | RNP APCH |
| TF | CR219 | - | 21.9 | 083°(082.7°) | - | -1200 | - | - | RNP APCH |
| TF | CR220 | - | 28.2 | 154°(153.2°) | - | 1200 | - | - | RNP APCH |

2. RNP HOLDING PROCEDURE

| Holding Fix | Fly- over | Inbound Course/Track °M(°T) | Magnetic Variation | Time (min) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|----------------|--------------|-----------------------------------|-----------------------|--------------------------|-------------------|-----------------|------------------------------|-------------|
| CR220 | Y | 231°(230.0°) | 0°45'W | 1 ≤ FL140 1.5 > FL140 | L | +1200 | -430 ≤ FL140 -445 > FL140 | RNP 1 |
| CR021 | Y | 297°(295.9°) | 0°45'W | 1 ≤ FL140 1.5 > FL140 | L | +1500 | -430 ≤ FL140 -445 > FL140 | RNP 1 |