

APCH procedure coding of RNP Y RWY 20R

1. RNP Y APPROACH RWY 20R FROM CR223

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	CR223	-	-	-	-	1200	-	-	RNP APCH
TF	CR201	-	39.1	337°(336.2°)	-	-	-	-	RNP APCH
TF	CR203	-	13.0	290°(288.9°)	-	+950	-	-	RNP APCH
TF	CR204	-	8.0	200°(198.9°)	-	650	-	-	RNP APCH
TF	MAPT (THR 20R)	Y	11.9	200°(198.9°)	-	29	-	5.2%	RNP APCH
DF	CR205	Y	-	-	-	+600	-	-	RNP APCH
DF	CR222	-	-	-	-	-	-	-	RNP APCH
TF	CR223	-	18.4	068°(067.5°)	-	1200	-	-	RNP APCH

2. RNP HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
CR223	Y	337°(336.2°)	0°45'W	1 ≤ FL140 1.5 > FL140	R	+1200	-430 ≤ FL140 -445 > FL140	RNP ACPH