

TAKE-OFF MINIMA FOR RWY 03/21

Take-off for RWY	ACFT CAT	RVR (M)	Visibility (M)
03	A, B, C, D	800	1 000
21	A, B, C, D	600	800

- Note:**
1. Take-off alternate aerodromes: Noi Bai, Cat Bi, Vinh
 2. When take-off alternate aerodrome can not be chosen, the operational minima for take-off shall be applied for landing minima at Van Don International Aerodrome

LANDING MINIMA FOR RWY 03/21

VOR/DME approach procedure for RWY 03	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	250		3 100

VOR/DME approach procedure for RWY 21	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	220		2 700

ILS approach procedure for RWY 03	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	100	800	1 000

ILS approach procedure for RWY 03 (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	250		3 100

ILS U, ILS V approach procedure for RWY 03	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	95	700	900
	C, D	100	800	1 000

ILS U, ILS V approach procedure for RWY 03 (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	250		3 100

ILS W, ILS X approach procedure for RWY 03	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	95	700	900
	C, D	100	800	1 000