

TAKE – OFF MINIMA FOR RWY 02L/R – 20 L/R

TAKE – OFF FOR RWY 02L/R – 20 L/R	ACFT CAT	Visibility /RVR (M)
	A, B, C, D	800

- Note:**
1. Take-off alternate aerodromes: Tan Son Nhat, Da Nang, Noi Bai and other appropriate aerodromes.
 2. When the ACFT can not choose any take-off alternate aerodrome as mentioned above, the landing minima as indicated in the below table will be applied to take-off minima

LANDING MINIMA FOR RWY 02L/R – 20 L/R

1. VOR approach procedures

VOR approach procedure for RWY 02L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	300	3 000
	C	400	4 500

VOR Y approach procedure for RWY 20L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	200	2 800
	C	200	3 000
	D	200	3 200

Circling VOR Y for RWY 20L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	280	4 500
	C	380	5 000
	D	800	6 000

VOR Z, VOR Y, VOR X approach procedure for RWY 20R	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	200	2 400
	C	200	3 400
	D	200	4 000

Circling VOR X, VOR Y, VOR Z for RWY 20R	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	280	4 500
	C	380	5 000
	D	800	6 000