

# APCH procedure coding of ILS X RWY 03

## 1. ILS X RWY 03: INITIAL APPROACH SEGMENT FROM VD901

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV SPEC
IF	VD901	-	-	-	-	+900	-	-	RNP 1
TF	VD902	-	16.7	269°(267.1°)	-	-	-	-	RNP 1
TF	VD031	-	9.3	298°(295.8°)	R	800	-	-	RNP 1

## 2. ILS X RWY 03: MISSED APPROACH SEGMENT

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV SPEC
IF	MAPT	Y	-	-	-	-	-	-	RNP 1
DF	VD900	Y	-	-	-	-	-	-	RNP 1
DF	VD901	-	-	-	R	900	-	-	RNP 1
HM	VD901	-	-	-	L	+900	-	-	RNP 1

## 3. RNP HOLDING PROCEDURE

HOLDING FIX	FLY- OVER	INBOUND COURSE/TRACK °M(°T)	MAGNETIC VARIATION	TIME (MIN)	TURN DIRECTION	ALTITUDE (M)	SPEED (KM/H)	NAV SPEC
VD901	Y	230°(228.2°)	+1.8	1 ≤ FL140 1.5 > FL140	L	+900	-430 ≤ FL140 -445 > FL140	RNP 1