

APCH procedure coding of RNP Y RWY 21

1. RNP APPROACH PROCEDURE RWY 21 FROM VD801

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV SPEC
IF	VD801	-	-	-	-	+900	-	-	RNP APCH
TF	VD802	-	23.1	350°(348.3°)	-	-	-	-	RNP APCH
TF	VD211	-	9.3	298°(295.9°)	L	790	-	-	RNP APCH
TF	VD210	-	7.4	208°(206.1°)	L	600	-	-	RNP APCH
TF	THR21	Y	11.1	208°(205.8°)	-	-	-	-5.2%	RNP APCH
DF	VD800	Y	-	-	-	-	-	-	RNP APCH
DF	VD801	-	-	-	L	900	-	-	RNP APCH
HM	VD801	-	-	-	R	+900	-	-	RNP APCH

2. RNP HOLDING PROCEDURE

HOLDING FIX	FLY- OVER	INBOUND COURSE/TRACK °M(°T)	MAGNETIC VARIATION	TIME (MIN)	TURN DIRECTION	ALTITUDE (M)	SPEED (KM/H)	NAV SPEC
VD801	Y	002°(360.0°)	+1.8	1 ≤ FL140 1.5 > FL140	R	+900	-430 ≤ FL140 -445 > FL140	RNP APCH