

CHUTU 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	CHUTU	-	-	0°45'W	-	-	-	-	-	RNP 1
2	TF	PANLU	-	097°(096.6°)	0°45'W	43.9	-	-2750 +2150	-	-	RNP 1

5. RNP HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
SIMME	Y	175°(174.5°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+FL120	-430 ≤ FL140 -445 > FL140	RNP 1
LIGUN	Y	243°(242.1°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+FL100	-430 ≤ FL140 -445 > FL140	RNP 1
BANKE	Y	081°(080.1°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+FL110	-430 ≤ FL140 -445 > FL140	RNP 1
CHUTU	Y	097°(096.6°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+FL110	-430 ≤ FL140 -445 > FL140	RNP 1
CR201	Y	290°(288.9°)	0°45'W	1 ≤ FL140 1.5 > FL140	R	+1500	-430 ≤ FL140 -445 > FL140	RNP 1
CR202	Y	199°(198.7°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+1200	-430 ≤ FL140 -445 > FL140	RNP 1
CR209	Y	109°(108.7°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+1850	-430 ≤ FL140 -445 > FL140	RNP 1