

Take-off minima for RWY 08/26

RWY 08/26	ACFT CAT	RVR (M)	Visibility (M)
	A, B, C		1 200

- Note:**
1. Take-off alternate aerodromes: Tan Son Nhat, Can Tho
 2. When take-off alternate aerodrome cannot be chosen, the operational minima for take-off will be the value for landing as appropriate.

Landing minima for RWY 08/26

VOR approach procedure for RWY 08	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	120		1 600
	C	120		1 800

VOR Z, Y procedure for RWY 26	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	115		1 600
	C	115		1 800

NDB approach procedure for RWY 08/26	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	200		2 000
	C	200		2 400

Circling for RWY 08/26	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	300		3 000

RNP approach procedures

RNP Z (LNAV/VNAV) approach procedures for RWY 08	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	85		1 200

RNP Z (LNAV) approach procedures for RWY 08	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	120		1 800

RNP Z, Y (LNAV/VNAV) approach procedures for RWY 26	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	85		1 200

RNP Z, Y (LNAV) approach procedures for RWY 26	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	120		1 800