

1. TABULAR DESCRIPTION

POTIX 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	-	-	076(075.6)	0	-	-	+125	-	4.0	RNP 1
020	DF	RG871	-	-	0	-	-	-	-	4.0	RNP 1
030	TF	AGOBI	-	052(052.2)	0	20.57	-	-1850 +1200	-	4.0	RNP 1
040	TF	POTIX	-	060(060.1)	0	31.13	-	-	-	-	RNP 1

TRN 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	-	-	076(075.6)	0	-	-	+125	-	4.0	RNP 1
020	DF	RG871	-	-	0	-	-	-	-	4.0	RNP 1
030	TF	AGOBI	-	052(052.2)	0	20.57	-	-1850 +1200	-	4.0	RNP 1
040	TF	TRN	-	092(091.9)	0	36.77	-	-	-	-	RNP 1

DADEM 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	-	-	076(075.6)	0	-	-	+125	-	-	RNP 1
020	DF	RG871	-	-	0	-	-	-	-	-	RNP 1
030	TF	RG872	-	345(345.4)	0	11.14	-	-	-410	-	RNP 1
040	TF	OMDES	-	347(346.8)	0	17.14	-	-1850	-	-	RNP 1
050	TF	DADEM	-	006(005.7)	0	74.08	-	@FL120	-	-	RNP 1

KISAN 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	-	-	076(075.6)	0	-	-	+125	-	3.8	RNP 1
020	DF	RG871	-	-	0	-	-	-	-	3.8	RNP 1
030	TF	RG872	-	345(345.4)	0	11.14	-	-	-410	3.8	RNP 1
040	TF	NISUM	-	292(292.4)	0	27.49	-	-1850	-	3.8	RNP 1
050	TF	KISAN	-	322(322.0)	0	51.40	-	@FL120	-	3.8	RNP 1

2. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
AGOBI	10°05'41"N	105°22'13"E
DADEM	10°53'44"N	105°13'41"E
KISAN	10°32'20"N	104°40'30"E
NISUM	10°10'23"N	104°57'52"E
OMDES	10°13'45"N	105°09'38"E
POTIX	10°14'05"N	105°37'00"E
RG871	09°58'51"N	105°13'19"E
RG872	10°04'42"N	105°11'47"E
TRN	10°05'00"N	105°42'20"E