

1. TABULAR DESCRIPTION

POTIX 1J DEPARTURE											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	–	–	256(255.6)	0	–	–	+125	–	4.8	RNP 1
020	DF	RG671	–	–	0	–	–	–	–	4.8	RNP 1
030	TF	RG672	–	345(345.4)	0	11.11	–	–	-410	4.8	RNP 1
040	TF	RG673	–	075(075.5)	0	21.67	–	+1850	–	4.8	RNP 1
050	TF	AGOBI	–	085(085.3)	0	17.75	–	@2450	–	3.4	RNP 1
060	TF	POTIX	–	060(060.1)	0	31.13	–	–	–	–	RNP 1

TRN 1J DEPARTURE											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	–	–	256(255.6)	0	–	–	+125	–	4.8	RNP 1
020	DF	RG671	–	–	0	–	–	–	–	4.8	RNP 1
030	TF	RG672	–	345(345.4)	0	11.11	–	–	-410	4.8	RNP 1
040	TF	RG673	–	075(075.5)	0	21.67	–	+1850	–	4.8	RNP 1
050	TF	AGOBI	–	085(085.3)	0	17.75	–	@2450	–	3.4	RNP 1
060	TF	TRN	–	092(091.9)	0	36.77	–	–	–	–	RNP 1

DADEM 1J DEPARTURE											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	–	–	256(255.6)	0	–	–	+125	–	–	RNP 1
020	DF	RG671	–	–	0	–	–	–	–	–	RNP 1
030	TF	RG672	–	345(345.4)	0	11.11	–	–	-410	–	RNP 1
040	TF	OMDES	–	036(035.8)	0	26.81	–	-1850	–	–	RNP 1
050	TF	DADEM	–	006(005.7)	0	74.08	–	@FL120	–	–	RNP 1

KISAN 1J DEPARTURE											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	–	–	256(255.6)	0	–	–	+125	–	4.2	RNP 1
020	DF	RG671	–	–	0	–	–	–	–	4.2	RNP 1
030	TF	RG672	–	345(345.4)	0	11.11	–	–	-410	4.2	RNP 1
040	TF	NISUM	–	339(339.5)	0	16.60	–	-1850	–	4.2	RNP 1
050	TF	KISAN	–	322(322.0)	0	51.40	–	@FL120	–	4.2	RNP 1