

**1. TABULAR DESCRIPTION**

POTIX 1L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	POTIX	-	-	0	-	-	-	-	RNP 1
020	TF	AGOBI	-	240(240.2)	0	31.13	-	-1500 +1200	-	RNP 1

TRN 1L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	TRN	-	-	0	-	-	-	-	RNP 1
020	TF	AGOBI	-	272(272.0)	0	36.77	-	-1500 +1200	-	RNP 1

DADEM 1L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DADEM	-	-	0	-	-	@FL110	-	RNP 1
020	TF	OMDES	-	186(185.7)	0	74.08	-	+2150	-	RNP 1
030	TF	RG613	-	141(141.0)	0	18.86	-	+1200	-	RNP 1

KISAN 1L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KISAN	-	-	0	-	-	@FL110	-	RNP 1
020	TF	NISUM	-	142(141.9)	0	51.40	-	+2150	-	RNP 1
030	TF	RG613	-	104(104.2)	0	34.42	-	+1200	-	RNP 1

**2. HOLDING PROCEDURES**

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
AGOBI	218(218.0)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP 1
OMDES	141(141.0)	0	1 ≤ FL140 1.5 > FL140	R	+2150	-425 ≤ FL140 -445 > FL140	RNP 1
NISUM	104(104.0)	0	1 ≤ FL140 1.5 > FL140	R	+2150	-425 ≤ FL140 -445 > FL140	RNP 1

**3. WAYPOINT LIST**

WAYPOINT ID	COORDINATES (WGS-84)	
AGOBI	10°05'41"N	105°22'13"E
DADEM	10°53'44"N	105°13'41"E
KISAN	10°32'20"N	104°40'30"E
NISUM	10°10'23"N	104°57'52"E
OMDES	10°13'45"N	105°09'38"E
POTIX	10°14'05"N	105°37'00"E
RG613	10°05'48"N	105°16'08"E
TRN	10°05'00"N	105°42'20"E