

1. TABULAR DESCRIPTION

BIVIM 1B TRANSITION										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	BIVIM	-	-	+2	-	-	+FL230	-	RNAV 1
020	TF	TOSCA	-	337(334.6)	+2	36.54	-	-	-490	RNAV 1
030	TF	NB501	-	256(254.3)	+2	25.92	-	-	-	RNAV 1
040	TF	NB502	-	276(274.3)	+2	27.79	-	-	-465	RNAV 1
050	TF	NB503	-	298(295.8)	+2	29.62	-	-	-	RNAV 1
060	TF	BISON	-	039(036.8)	+2	76.78	-	+FL170	-	RNAV 1

2. HOLDING PROCEDURE

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
BIVIM	336(334.0)	+2	1.5	L	-FL280 +FL230	-490	RNAV 1

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
BISON	20°26'00"N	105°38'30"E
BIVIM	19°30'34"N	106°06'28"E
NB501	19°44'38"N	105°43'12"E
NB502	19°45'45"N	105°27'20"E
NB503	19°52'43"N	105°12'03"E
TOSCA	19°48'27"N	105°57'29"E