

Procedure coding (cont.)

9. RNAV RWY 29R: LENNU ONE BRAVO DEPARTURE (LENNU 1B)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	NB290	-	289(286.7)	+2.0	-	-	+1500	-	-	RNAV 1
2	TF	LENNU	-	278(275.5)	+2.0	40.2	-	+FL140	-	-	RNAV 1

BQ 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	LENNU	-	-	+2.0	-	-	+FL140	-	-	RNAV 1
2	TF	BQ	-	265(263.3)	+2.0	113.6	-	-	-	-	RNAV 1

10. RNAV RWY 29R: JULUN ONE DELTA DEPARTURE (JULUN 1D)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	NB290	-	289(286.7)	+2.0	-	-	+1500	-	-	RNAV 1
2	TF	JULUN	-	349(347.2)	+2.0	51.2	-	+FL160	-	-	RNAV 1

DILEN 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	JULUN	-	-	+2.0	-	-	+FL160	-	-	RNAV 1
2	TF	DILEN	-	012(010.3)	+2.0	39.9	-	-	-	-	RNAV 1