

Procedure coding (cont.)

5. RNAV RWY 11L: HUVAN ONE MIKE ARRIVAL (HUVAN 1M)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	HUVAN	-	-	+2.0	-	-	-FL110 +FL100	-	-	RNAV 1
2	TF	KHARO	-	150(148.4)	+2.0	25.4	-	-FL110	-465	-	RNAV 1
3	TF	NB374	-	166(163.9)	+2.0	20.7	-	-	-	-	RNAV 1
4	TF	NB375	-	137(134.5)	+2.0	21.4	-	-	-	-	RNAV 1
5	TF	NB376	-	107(104.5)	+2.0	21.3	-	-	-	-	RNAV 1
6	TF	MIMON	-	002(359.6)	+2.0	21.3	-	-	-	-	RNAV 1
7	TF	SONTA	-	002(359.6)	+2.0	20.0	-	+1850	-410	-	RNAV 1
8	TF	DONMO	-	346(343.5)	+2.0	17.8	-	+1200	-370	-	RNAV 1
9	TF	NB360	-	016(014.3)	+2.0	11.4	-	+600	-	-	RNAV 1

6. RNAV HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
TAMDA	Y	118(116.1)	+2.0	1 ≤ FL140 1.5 > FL140	R	+FL120	-430 ≤ FL140 -445 > FL140	RNAV 1
HAKAO	Y	232(230.4)	+2.0	1 ≤ FL140 1.5 > FL140	R	+2150	-430 ≤ FL140 -445 > FL140	RNAV 1
BISON	Y	001(359.4)	+2.0	1 ≤ FL140 1.5 > FL140	L	+2450	-430 ≤ FL140 -445 > FL140	RNAV 1
MUCHI	Y	071(069.4)	+2.0	1 ≤ FL140 1.5 > FL140	R	+FL100	-430 ≤ FL140 -445 > FL140	RNAV 1
HUVAN	Y	150(148.4)	+2.0	1 ≤ FL140 1.5 > FL140	L	+FL110	-430 ≤ FL140 -445 > FL140	RNAV 1