

ILS Y, ILS Z approach procedures for RWY 29R (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	140		2 000
	C	140		2 400
	D	140		2 800

## 2. VOR approach procedures

VOR Z (VOR/DME NOB) approach procedure for RWY 11L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	140		1 600
	C	140		2 000
	D	140		2 400

VOR Y (VOR/DME VPH) approach procedure for RWY 11L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	150		2 400
	D	150		2 800

VOR (VOR/DME NOB) approach procedure for RWY 29L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	140		2 000
	C	140		2 400
	D	140		2 800

VOR Y (VOR/DME NOB) approach procedure for RWY 29R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	140		2 000
	C	140		2 400
	D	140		2 800

Circling RWY 11L/29R and RWY 11R/29L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A	200		2 000
	B	400		4 000
	C	500		5 000
	D	600		6 000