

**1. TABULAR DESCRIPTION**

**INITIAL APPROACH**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	LINEN	–	–	+1	–	–	+1200	–	–	RNP 1
020	TF	IBUTA	–	072(071.1)	+1	25.49	–	–	-380	–	RNP 1
030	TF	TH501	–	121(119.8)	+1	12.96	–	+950	–	–	RNP 1

**MISSED APPROACH**

010	CA	–	–	225(224.0)	+1	–	–	+450	–	–	RNP 1
020	DF	LINEN	–	–	+1	–	R	@1200	-445	–	RNP 1
030	HM	LINEN	–	072(071.1)	+1	–	L	+1200	-380	–	RNP 1

**2. HOLDING PROCEDURES**

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
LINEN	072(071.1)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-380 ≤ FL140 -445 > FL140	RNP 1

**3. WAYPOINT LIST**

WAYPOINT/FIX	COORDINATES (WGS-84)	
LINEN	13°12'16.0"N	109°06'31.0"E
IBUTA	13°16'44.8"N	109°19'52.1"E
TH501 - BRG 030.83° ITH LLZ/D11.25 ITH DME	13°13'14.9"N	109°26'05.7"E
TH502 - BRG 030.83° ITH LLZ/D6.12 ITH DME	13°08'46.5"N	109°23'28.5"E
RWY21	13°03'35.32"N	109°20'26.40"E
ITH GP/DME	13°03'28.5"N	109°20'18.2"E
ITH LLZ	13°02'04.8"N	109°19'33.5"E