

## TAKE-OFF MINIMA FOR RWY 03/21

TAKE - OFF FOR RWY 03/21	ACFT CAT	RVR (M)	Visibility (M)
	A, B		1 100
	C, D		1 300

- Note:**
1. Take-off alternate aerodromes: Cam Ranh, Buon Ma Thuot, Phu Cat, Da Nang, Tan Son Nhat.
  2. When take-off alternate aerodrome cannot be chosen, the AD operating minima for take-off will be the value for landing as appropriate.

## LANDING MINIMA FOR RWY 03/21

ILS Z, ILS Y, ILS X approach procedure for RWY 21	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	115		1 900
	C, D	120		2 000

ILS Z, ILS Y, ILS X approach procedure for RWY 21 (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	195		2 800

RNP Z, RNP Y (LNAV/VNAV) approach procedure for RWY 21	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	120		2 000

RNP Z, RNP Y (LNAV) approach procedure for RWY 21	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	155		2 600

RNP Z, RNP Y (LNAV) approach procedure for RWY 03	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	155		2 600

VOR Z approach procedure for RWY 21	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	195		2 800

Circling for RWY 03/21	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	265		3 700
	C	430		5 000
	D	605		6 000