

APCH procedure coding of RNP Y RWY 02R**1. RNP Y APPROACH PROCEDURE RWY 02R FROM CR220**

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV SPEC
IF	CR220	-	-	-	-	1200	-	-	RNP APCH
TF	CR021	-	29.2	259°(258.3°)	-	-	-	-	RNP APCH
TF	CR822	-	14.5	297°(295.9°)	-	795	-	-	RNP APCH
TF	CR823	-	6.1	020°(018.8°)	-	650	-	-	RNP APCH
TF	MAPT (THR 02R)	Y	10.3	020°(018.8°)	-	20	-	6.1%	RNP APCH
DF	CR818	-	-	-	-	-	-	-	RNP APCH
TF	CR219	-	20.6	089°(088.6°)	-	-1200	-	-	RNP APCH
TF	CR220	-	28.2	154°(153.2°)	-	1200	-	-	RNP APCH

2. RNP HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
CR220	Y	231°(230.0°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+1200	-430 ≤ FL140 -445 > FL140	RNP 1