

**APCH procedure coding of RNP Z RWY 02L****1. RNP Z APPROACH PROCEDURE RWY 02L**

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV PER
IF	CR021	-	-	-	-	1500	-	-	RNP APCH
TF	CR022	-	14.8	297°(295.9°)	-	+795	-	-	RNP APCH
TF	CR023	-	6.2	020°(018.8°)	-	652	-	-	RNP APCH
TF	MAPT RWY 02L	Y	7.9	020°(018.9°)	-	180	-	6.0%	RNP APCH
DF	CR218	-	-	-	-	-	-	-	RNP APCH
TF	CR219	-	21.9	083°(082.7°)	-	-1200	-	-	RNP APCH
TF	CR220	-	28.2	154°(153.2°)	-	1200	-	-	RNP APCH

**2. RNP HOLDING PROCEDURE**

Holding Fix	Fly- over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
CR220	Y	231°(230.0°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+1200	-430 ≤ FL140 -445 > FL140	RNP 1
CR021	Y	297°(295.9°)	0°45'W	1 ≤ FL140 1.5 > FL140	L	+1500	-430 ≤ FL140 -445 > FL140	RNP 1