

AD OPERATING MINIMA

VVCR WEATHER MNM
VVCR

ILS X, ILS Y approach procedure for RWY 20L in case of GP unserviceable	ACFT CAT	Ceiling (M)	Visibility (M)	RVR (M)
	A, B, C, D	190	3 000	

ILS Z approach procedure for RWY 20L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	115	1 600
	C	120	1 800
	D	125	1 800

ILS Z approach procedure for RWY 20L in case of GP unserviceable	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B, C, D	200	3 200

Circling ILS Z for RWY 20L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	280	4 500
	C	380	5 000
	D	800	6 000

2. RNP APCH Procedure

RNP Z, RNP Y APCH RWY 02L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	180	2 400
	C	180	3 400
	D	180	4 000

RNP Z, RNP Y APCH RWY 20R	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	185	2 400
	C	185	3 400
	D	185	4 000

RNP Y, RNP Z APCH RWY 20L	ACFT CAT	Ceiling (M)	Visibility (M)	RVR (M)
	A, B	150	2 400	
	C	150	2 800	
	D	150	3 000	

RNP Y, RNP Z APCH RWY 02R	ACFT CAT	Ceiling (M)	Visibility (M)	RVR (M)
	A, B	155	2 100	
	C	155	2 300	
	D	155	2 500	

3. VOR Approach Procedure

VOR approach procedure for RWY 02L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	300	3 000
	C	400	4 500

VOR Y approach procedure for RWY 20L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	200	2 800
	C	200	3 000
	D	200	3 200

Circling VOR Y for RWY 20L	ACFT CAT	Ceiling (M)	Visibility (M)
	A, B	280	4 500
	C	380	5 000
	D	800	6 000