

SID and Transition coding of RNP RWY 20R**1. RNP 1 RWY 20R: NIHOA ONE BRAVO DEPARTURE (NIHOA 1B)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	MaxSpeed (km/h)	VPA/TCH	Nav Spec
1	CF	CR400	-	200°(198.8°)	0°45' W	13.9	-	+600	-	-	RNP 1
2	TF	CR401	-	110°(108.8°)	0°45' W	13.0	-	-	-	-	RNP 1
3	TF	CR402	-	019°(018.6°)	0°45' W	20.4	-	+2750	- 465	-	RNP 1
4	TF	CR406	-	337°(335.8°)	0°45' W	22.4	-	+FL120	-	-	RNP 1
5	TF	NIHOA	-	337°(335.8°)	0°45' W	20.3	-	-	-	-	RNP 1

NOTE: MIN PDG 5.5% UNTIL PASSING FL120.**2. RNP 1 RWY 20R: KOPOM ONE ALPHA DEPARTURE (KOPOM 1A)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	MaxSpeed (km/h)	VPA/TCH	Nav Spec
1	CF	CR400	-	200°(198.8°)	0°45' W	13.9	-	+600	-	-	RNP 1
2	TF	CR401	-	110°(108.8°)	0°45' W	13.0	-	-	-	-	RNP 1
3	TF	KOPOM	-	055°(054.4°)	0°45' W	39.8	-	+2750	-	-	RNP 1

NOTE: MIN PDG 5.5% UNTIL PASSING 2750M.**NITOM1B TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	MaxSpeed (km/h)	VPA/TCH	Nav Spec
1	IF	KOPOM	-	-	0°45' W	-	-	+2750	-	-	RNP 1
2	TF	TEMMA	-	063°(062.0°)	0°45' W	36.3	-	-	-	-	RNP 1
3	TF	NITOM	-	054°(053.6°)	0°45' W	102.8	-	-	-	-	RNP 1

3. RNP 1 RWY 20R: ANKIN ONE BRAVO DEPARTURE (ANKIN 1B)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	MaxSpeed (km/h)	VPA/TCH	Nav Spec
1	CF	CR400	-	200°(198.8°)	0°45' W	13.9	-	+600	-	-	RNP 1
2	TF	CR401	-	110°(108.8°)	0°45' W	13.0	-	-	-	-	RNP 1
3	TF	CR402	-	019°(018.6°)	0°45' W	20.4	-	+2750	-	-	RNP 1
4	TF	CR403	-	294°(293.1°)	0°45' W	13.0	-	-	- 465	-	RNP 1
5	TF	ANKIN	-	224°(222.8°)	0°45' W	45.6	-	-	-	-	RNP 1

NOTE: MIN PDG 5.5% UNTIL PASSING FL140.**4. RNP 1 RWY 20R: BANKE ONE BRAVO DEPARTURE (BANKE 1B)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	MaxSpeed (km/h)	VPA/TCH	Nav Spec
1	CF	CR400	-	200°(198.8°)	0°45' W	13.9	-	+600	-	-	RNP 1
2	TF	CR401	-	110°(108.8°)	0°45' W	13.0	-	-	-	-	RNP 1
3	TF	CR402	-	019°(018.6°)	0°45' W	20.4	-	+2750	-	-	RNP 1
4	TF	CR403	-	294°(293.1°)	0°45' W	13.0	-	-	- 465	-	RNP 1
5	TF	CR404	-	248°(247.5°)	0°45' W	18.2	-	+FL140	-	-	RNP 1
6	TF	BANKE	-	248°(247.4°)	0°45' W	25.6	-	-	-	-	RNP 1

NOTE: MIN PDG 5.5% UNTIL PASSING FL140.**5. RNP 1 RWY 20R: SOTEN ONE BRAVO DEPARTURE (SOTEN 1B)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	MaxSpeed (km/h)	VPA/TCH	Nav Spec
1	CF	CR400	-	200°(198.8°)	0°45' W	13.9	-	+600	-	-	RNP 1
2	TF	CR401	-	110°(108.8°)	0°45' W	13.0	-	-	-	-	RNP 1
3	TF	CR402	-	019°(018.6°)	0°45' W	20.4	-	+2750	- 465	-	RNP 1
4	TF	CR405	-	294°(293.1°)	0°45' W	22.4	-	+FL120	-	-	RNP 1
5	TF	SOTEN	-	294°(293.1°)	0°45' W	29.5	-	-	-	-	RNP 1

NOTE: MIN PDG 5.5% UNTIL PASSING FL120.