

Procedure coding

1. RNP 1 RWY 09: XILGA ONE ALPHA DEPARTURE (XILGA 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	PB109	Y	094 (093.2)	+1.0	13.0	-	-1200 +900	-	RNP 1
2	TF	XILGA	-	094 (093.2)	+1.0	15.5	-	+1850	-	RNP 1

DAN 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	XILGA	-	-	+1.0	-	-	+1850	-	RNP 1
2	TF	DAN	-	149 (147.9)	+1.0	43.4	R	-FL130 +FL120	-	RNP 1

2. RNP 1 RWY 09: NAKHE ONE BRAVO DEPARTURE (NAKHE 1B)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	PB109	Y	094 (093.2)	+1.0	13.0	-	-1200 +900	-440	RNP 1
2	DF	PB209	-	-	+1.0	-	L	+2150	-	RNP 1
3	TF	PB309	-	275 (274.4)	+1.0	15.0	L	+2750	-450	RNP 1
4	TF	PB409	-	196 (195.0)	+1.0	19.2	L	+FL110	-	RNP 1
5	TF	NAKHE	-	196 (195.0)	+1.0	28.8	-	-	-	RNP 1

SADIN 1C TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	NAKHE	-	-	+1.0	-	-	-	-	RNP 1
2	TF	SADIN	-	153 (152.1)	+0.7	134.0	-	+FL120	-	RNP 1

VILOT 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	NAKHE	-	-	+1.0	-	-	-	-	RNP 1
2	TF	VILOT	-	156 (155.7)	+0.7	135.1	-	+FL120	-	RNP 1