

Procedure coding

1. RNP RWY 07L: APPROACH FROM SAMDU

| RCMD.PATH TERMINATOR | FIX ID (WPT NAME) | FLY- OVER | DISTANCE (km) | TRACK | | TURN DIRECTION | ALTITUDE (m) | SPEED LIMIT (IAS) (km/h) | VER ANGLE | NAV SPEC |
|-------------------------|-------------------------|--------------|------------------|--------------|---------------|-------------------|-----------------|--------------------------------|--------------|----------|
| | | | | MAG TRACK | TRUE TRACK | | | | | |
| IF | SAMDU | - | - | - | - | - | -1500 | -425 | - | RNP APCH |
| TF | TS526 | - | 9.3 | 025 | 024.1 | - | +600 | - | - | RNP APCH |
| TF | TS524 | - | 6.5 | 070 | 069.1 | - | @600 | - | - | RNP APCH |
| TF | RW07L | Y | 11.2 | 070 | 069.1 | - | - | - | -3° | RNP APCH |
| CF | TS594 | - | 17.1 | 070 | | - | - | - | - | RNP APCH |
| TF | TS596 | - | 13.3 | 160 | 159.1 | - | - | - | - | RNP APCH |
| TF | TUNBI | - | 25.6 | 190 | 188.8 | - | @900 | -425 | - | RNP APCH |
| HM | TUNBI | - | - | 001 | 360.0 | L | @900 | -405 | - | RNP APCH |

2. RNAV HOLDING PROCEDURE

| Holding Fix | Fly- over | Inbound Course/Track °M(°T) | | Magnetic Variation | Time (s) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|-------------|--------------|-----------------------------------|-------|-----------------------|-------------|-------------------|-----------------|-----------------|----------|
| TUNBI | Y | 001 | 360.0 | +1 | 60 | L | @900 | -405 | RNAV 1 |