

## Procedure coding

### 1. ILS W RWY 07R

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (km)	TRACK		TURN DIRECTION	ALTITUDE (m)	SPEED LIMIT (IAS) km/h	VER ANGLE	NAV SPEC
				MAG TRACK	TRUE TRACK					
IF	SAMDU	-	-	-	-	-	-1500	-425	-	RNAV 1
TF	TS516	-	9.2	028	026.9	-	+600	-	-	RNAV 1
TF	TS512	-	7.1	070	069.1	-	@600	-	-	RNAV 1
CF	RW07R	Y	-	070	069.1	-	@25	-	-3.0°	X
CF	TS554	-	-	070	069.1	-	-	-	-	RNAV 1
TF	TS556	-	10.0	340	339.1	-	-	-	-	RNAV 1
TF	TS500	-	35.8	278	276.7	-	@900	-410	-	RNAV 1
HM	TS500	-	-	295	294.0	L	@900	-405	-	RNAV 1

### 2. RNAV HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/Track °M(°T)		Magnetic Variation	Time (s)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
TS500	-	295	294.0	+1	60	L	@900	-405	RNAV 1