

Procedure coding**1. RNP Y RWY 07L**

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (km)	TRACK		TURN DIRECTION	ALTITUDE (m)	SPEED LIMIT (IAS) (km/h)	VER ANGLE	NAV SPEC
				MAG TRACK	TRUE TRACK					
IF	SAMDU	-	-	-	-	-	-1500	-425	-	RNP APCH
TF	TS526	-	9.3	025	024.1	-	+600	-	-	RNP APCH
TF	TS524	-	6.5	070	069.1	-	@600	-	-	RNP APCH
TF	TS520 (MAPT)	Y	9.9	070	069.1	-	@92	-	-3°	RNP APCH
CF	TS552	-	-	070	069.1	-	-	-	-	RNP APCH
TF	TS556	-	9.7	347	345.8	-	-	-	-	RNP APCH
TF	TS500	-	35.8	278	276.7	-	@900	-410	-	RNP APCH
HM	TS500	-	-	295	294.0	L	@900	-405	-	RNP APCH

2. RNAV HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/Track °M(°T)		Magnetic Variation	Time (s)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
TS500	-	295	294.0	+1	60	L	@900	-405	RNP APCH