

## Procedure coding

### 1. RNP Y RWY 07R

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (km)	TRACK		TURN DIRECTION	ALTITUDE (m)	SPEED LIMIT (IAS) km/h	VER ANGLE	NAV SPEC
				MAG TRACK	TRUE TRACK					
IF	SAMDU	-	-	-	-	-	-1500	-425	-	RNP APCH
TF	TS516	-	9.2	028	026.9	-	+600	-	-	RNP APCH
TF	TS514	-	6.9	070	069.1	-	@600	-	-	RNP APCH
TF	TS510 (MAPT)	Y	9.4	070	069.1	-	@115	-	-3°	RNP APCH
CF	TS554	-	-	070	069.1	-	-	-	-	RNP APCH
TF	TS556	-	10.0	340	339.1	-	-	-	-	RNP APCH
TF	TS500	-	35.8	278	276.7	-	@900	-410	-	RNP APCH
HM	TS500	-	-	295	294.0	L	@900	-405	-	RNP APCH

### 2. RNAV HOLDING PROCEDURE

HOLDING FIX	FLY- OVER	INBOUND COURSE/TRACK °M(°T)		MAGNETIC VARIATION	TIME (S)	TURN DIRECTION	ALTITUDE (m)	SPEED (km/h)	NAV SPEC
TS500	-	295	294.0	+1	60	L	@900	-405	RNP APCH