

## AD OPERATING MINIMA

TAN SON NHAT WEATHER MNM  
VVTS

## 4. RNP approach procedures

RNP approach procedure (LNAV/VNAV) for RWY 25L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	110	900	1 100
	C, D	115	1 000	1 400

RNP approach procedure (LNAV) for RWY 25L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	145	1 500	2 000
	C, D	145	1 500	2 200

RNP approach procedure (LNAV/VNAV) for RWY 25R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	100	1 100	1 300
	C, D	115	1 300	1 800

RNP approach procedure (LNAV) for RWY 25R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	150	1 500	2 200
	C, D	150	1 800	2 600

RNP approach procedure (LNAV/VNAV) for RWY 07L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	100	1 000	1 200
	C, D	105	1 100	1 500

RNP approach procedure (LNAV) for RWY 07L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	140	1 500	2 000
	C, D	140	1 700	2 400

RNP approach procedure (LNAV/VNAV) for RWY 07R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	100	1 100	1 300
	C, D	110	1 200	1 600

RNP approach procedure (LNAV) for RWY 07R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	135	1 500	2 000
	C, D	135	1 600	2 400

RNP Y (LNAV/VNAV) approach procedure for RWY 07L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	105	1 100	1 500
	C, D	110	1 200	1 600

RNP Y(LNAV) approach procedure for RWY 07L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	140	1 500	2 000
	C, D	140	1 700	2 400

RNP Y (LNAV/VNAV) approach procedure for RWY 25L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	120	1 100	1 400
	C, D	125	1 200	1 500

RNP Y (LNAV) approach procedure for RWY 25L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	150	1 500	2 200
	C, D	150	1 800	2 600