

Procedure coding (cont.)**DOVIN TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	TANOS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	DOVIN	-	034 (032.7)	1° W	158.1	-	-	-	-	RNAV1

LKH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	TANOS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	LKH	-	045 (044.3)	1° W	161.0	-	-	-	-	RNAV1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	TANOS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	PTH	-	075 (073.9)	1° W	85.2	-	+FL250	-	-	RNAV1

10. RNAV RWY 25R: ANTRI ONE DELTA DEPARTURE (ANTRI 1D)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	248 (247.3)	1° W	12.1	L	-	-	-	RNAV1
2	TF	TS017	-	172 (171.0)	1° W	28.7	L	-3050	-	-	RNAV1
3	TF	TS018	-	082 (081.0)	1° W	22.0	L	+3650	-	-	RNAV1
4	TF	TS019	-	051 (050.0)	1° W	32.0	L	-	-	-	RNAV1
5	TF	ANTRI	-	030 (028.7)	1° W	54.0	L	-	-	-	RNAV1

PATMA TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	ANTRI	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	PATMA	-	027 (025.6)	1° W	144.2	-	+FL290	-	-	RNAV1

11. RNAV RWY 25R: BACHU ONE GOLF DEPARTURE (BACHU 1G)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	248 (247.3)	1° W	12.1	L	-	-	-	RNAV1
2	TF	TS020	-	250 (249.0)	1° W	26.5	R	-3350 +1250	-	-	RNAV1
3	TF	BACHU	-	252 (251.1)	1° W	34.9	R	-	-	-	RNAV1

12. RNAV RWY 25R: KADUM ONE GOLF DEPARTURE (KADUM 1G)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	248 (247.3)	1° W	12.1	L	-	-410	-	RNAV1
2	TF	TS016	-	340 (339.0)	1° W	16.7	R	-	-	-	RNAV1
3	TF	KADUM	-	053 (052.1)	1° W	80.1	R	-	-	-	RNAV1

PATMA TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	KADUM	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	PATMA	-	038 (037.0)	1° W	136.0	-	+FL290	-	-	RNAV1