

Procedure coding (cont.)**13. RNAV RWY 25R: ENPAS ONE GOLF DEPARTURE (ENPAS 1G)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	248 (247.3)	1° W	12.1	L	-	-	-	RNAV1
2	TF	TS020	-	250 (249.0)	1° W	26.5	R	-3350 +1250	-	-	RNAV1
3	TF	ENPAS	-	215 (214.3)	1° W	38.4	L	-	-	-	RNAV1

ANHOA TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	ENPAS	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	ANHOA	-	199 (198.2)	1° W	71.3	-	+FL200	-	-	RNAV1

14. RNAV RWY 25R: LANHI ONE GOLF DEPARTURE (LANHI 1G)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	248 (247.3)	1° W	12.1	L	-	-	-	RNAV1
2	TF	TS017	-	172 (171.0)	1° W	28.7	L	-3050	-	-	RNAV1
3	TF	TS018	-	082 (081.0)	1° W	22.0	L	+3650	-	-	RNAV1
4	TF	LANHI	-	110 (108.9)	1° W	48.2	R	-	-	-	RNAV1

ELSAS TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	LANHI	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	ELSAS	-	128 (127.3)	1° W	49.2	-	+FL250	-	-	RNAV1

15. RNAV RWY 25R: XOBAY ONE ECHO DEPARTURE (XOBAY 1E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	248 (247.3)	1° W	12.1	L	-	-	-	RNAV1
2	TF	TS017	-	172 (171.0)	1° W	28.7	L	-3050	-	-	RNAV1
3	TF	XOBAY	-	171 (170.0)	1° W	42.2	R	-	-	-	RNAV1

NIXIV TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	XOBAY	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	NIXIV	-	182 (180.7)	1° W	82.6	-	+FL200	-	-	RNAV1

16. RNAV RWY 25R: MISAN ONE GOLF DEPARTURE (MISAN 1G)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	CF	TS015	-	248 (247.3)	1° W	12.1	L	-	-	-	RNAV1
2	TF	TS020	-	250 (249.0)	1° W	26.5	R	-3350 +1250	-	-	RNAV1
3	TF	MISAN	-	232 (231.2)	1° W	36.3	L	-	-	-	RNAV1

TRN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	MISAN	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TRN	-	222 (220.7)	1° W	57.9	-	-	-	-	RNAV1