

Procedure coding (cont.)**TRN TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	TRN	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	BITIS	-	072 (071.2)	1° W	62.8	-	-	-	-	RNAV1

3. RNAV RWY 25L: SAPEN TWO MIKE ARRIVAL (SAPEN 2M)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	SAPEN	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS012	-	141 (139.7)	1° W	57.5	-	+3650	-	-	RNAV1
3	TF	TS011	-	070 (069.0)	1° W	17.4	L	+3350	-	-	RNAV1
4	TF	TS010	-	070 (069.0)	1° W	18.3	-	-3050	-410	-	RNAV1
5	TF	TS009	-	160 (159.0)	1° W	26.5	R	-	-410	-	RNAV1
6	TF	TS005	-	070 (069.0)	1° W	13.0	L	-	-370	-	RNAV1
7	TF	TS004	-	340 (339.0)	1° W	7.4	L	+900	-370	-	RNAV1
8	TF	TS003	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
9	TF	TS002	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
10	TF	TS001	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
11	TF	SOKAN	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
12	TF	XIMLA	-	275 (273.8)	1° W	10.5	L	+750	-370	-	RNAV1

4. RNAV RWY 25L: VICAL TWO CHARLIE ARRIVAL (VICAL 2C)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	VICAL	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS014	-	025 (023.8)	1° W	29.5	-	-3350	-	-	RNAV1
3	TF	TS009	-	025 (024.0)	1° W	15.2	-	-3050	-410	-	RNAV1
4	TF	TS005	-	070 (069.0)	1° W	13.0	R	-	-370	-	RNAV1
5	TF	TS004	-	340 (339.0)	1° W	7.4	L	+900	-370	-	RNAV1
6	TF	TS003	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
7	TF	TS002	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
8	TF	TS001	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
9	TF	SOKAN	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
10	TF	XIMLA	-	275 (273.8)	1° W	10.5	L	+750	-370	-	RNAV1

NIXIV TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	NIXIV	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	VICAL	-	010 (008.7)	1° W	84.3	-	-	-	-	RNAV1

5. RNAV RWY 25R: BAOMY TWO GOLF ARRIVAL (BAOMY 2G)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA/TCH	Nav Spec
1	IF	BAOMY	-	-	1° W	-	-	-	-	-	RNAV1
2	TF	TS008	-	251 (249.9)	1° W	30.4	-	-3050 +1200	-410	-	RNAV1
3	TF	TS007	-	160 (159.0)	1° W	28.3	L	-	-410	-	RNAV1
4	TF	TS006	-	250 (249.0)	1° W	13.0	R	-	-370	-	RNAV1
5	TF	TS005	-	340 (339.0)	1° W	7.4	R	-	-370	-	RNAV1
6	TF	TS004	-	340 (339.0)	1° W	7.4	-	+900	-370	-	RNAV1
7	TF	TS003	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
8	TF	TS002	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
9	TF	TS001	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
10	TF	SOKAN	-	340 (339.0)	1° W	7.4	-	-	-370	-	RNAV1
11	TF	OMKAS	-	277 (275.6)	1° W	10.6	L	+750	-370	-	RNAV1