

Procedure coding**1. RWY 25L/R - RNAV 1: BITIS TWO HOTEL ARRIVAL (BITIS 2H)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	BITIS	-	-	+1	-	-	-	-	RNAV 1
2	TF	NOKUM	-	047 (046.5)	+1	50.7	-	+3650	-	RNAV 1
3	TF	TS492	-	113 (111.9)	+1	13.0	-	+3050	-	RNAV 1
4	TF	LETRO	-	113 (111.9)	+1	18.1	-	@2150	-460	RNAV 1
5	TF	VANLI	-	077 (075.9)	+1	14.4	-	-	-	RNAV 1
6	TF	TS488	-	069 (068.5)	+1	14.8	-	-	-	RNAV 1
7	TF	RUNSI	-	055 (053.5)	+1	6.4	-	@2150	-	RNAV 1
8	TF	TS458	-	044 (043.0)	+1	8.5	-	-	-	RNAV 1
9	TF	TS456	-	029 (027.9)	+1	12.9	-	-	-	RNAV 1
10	TF	TS454	-	011 (009.8)	+1	12.9	-	@2150	-	RNAV 1
11	TF	SOKAN	-	272 (270.7)	+1	40.7	-	-1500 +730	-425	RNAV 1

TRN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TRN	-	-	+1	-	-	-	-	RNAV 1
2	TF	BITIS	-	072 (071.2)	+1	62.8	-	-	-	RNAV 1

2. RWY 25L/R - RNAV 1: ELSAS TWO HOTEL ARRIVAL (ELSAS 2H)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	ELSAS	-	-	+1	-	-	-	-	RNAV 1
2	TF	GOMIN	-	320 (319.1)	+1	51.0	-	-	-	RNAV 1
3	TF	RUNSI	-	320 (319.0)	+1	15.7	-	@2150	-460	RNAV 1
4	TF	TS458	-	044 (043.0)	+1	8.5	-	-	-	RNAV 1
5	TF	TS456	-	029 (027.9)	+1	12.9	-	-	-	RNAV 1
6	TF	TS454	-	011 (009.8)	+1	12.9	-	@2150	-	RNAV 1
7	TF	SOKAN	-	272 (270.7)	+1	40.7	-	-1500 +730	-425	RNAV 1

3. RWY 25L/R - RNAV 1: SAPEN TWO HOTEL ARRIVAL (SAPEN 2H)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	SAPEN	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS498	-	139 (137.8)	+1	43.1	-	+4550	-	RNAV 1
3	TF	TS496	-	139 (137.8)	+1	7.4	-	+4250	-	RNAV 1
4	TF	NOKUM	-	139 (137.8)	+1	14.8	-	+3650	-	RNAV 1
5	TF	TS492	-	113 (111.9)	+1	13.0	-	+3050	-	RNAV 1
6	TF	LETRO	-	113 (111.9)	+1	18.1	-	@2150	-460	RNAV 1
7	TF	VANLI	-	077 (075.9)	+1	14.4	-	-	-	RNAV 1
8	TF	TS488	-	069 (068.5)	+1	14.8	-	-	-	RNAV 1
9	TF	RUNSI	-	055 (053.5)	+1	6.4	-	@2150	-	RNAV 1
10	TF	TS458	-	044 (043.0)	+1	8.5	-	-	-	RNAV 1
11	TF	TS456	-	029 (027.9)	+1	12.9	-	-	-	RNAV 1
12	TF	TS454	-	011 (009.8)	+1	12.9	-	@2150	-	RNAV 1
13	TF	SOKAN	-	272 (270.7)	+1	40.7	-	-1500 +730	-425	RNAV 1

4. RWY 25L/R - RNAV 1: VICAL THREE HOTEL ARRIVAL (VICAL 3H)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VICAL	-	-	+1	-	-	-	-	RNAV 1
2	TF	LETRO	-	017 (016.3)	+1	38.1	-	@2150	-460	RNAV 1
3	TF	VANLI	-	077 (075.9)	+1	14.4	-	-	-	RNAV 1
4	TF	TS488	-	069 (068.5)	+1	14.8	-	-	-	RNAV 1
5	TF	RUNSI	-	055 (053.5)	+1	6.4	-	@2150	-	RNAV 1
6	TF	TS458	-	044 (043.0)	+1	8.5	-	-	-	RNAV 1
7	TF	TS456	-	029 (027.9)	+1	12.9	-	-	-	RNAV 1
8	TF	TS454	-	011 (009.8)	+1	12.9	-	@2150	-	RNAV 1
9	TF	SOKAN	-	272 (270.7)	+1	40.7	-	-1500 +730	-425	RNAV 1