

Procedure coding**1. RWY 25L/R - RNAV 1: BITIS TWO JULIETT ARRIVAL (BITIS 2J)**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	BITIS	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS484	-	017 (016.0)	+1	68.3	-	+4550	-	RNAV 1
3	TF	TS482	-	017 (016.0)	+1	23.2	-	+3650	-	RNAV 1
4	TF	BUTGA	-	049 (047.6)	+1	37.5	-	+2150	-460	RNAV 1
5	TF	NUNGO	-	095 (094.0)	+1	12.2	-	@2150	-	RNAV 1
6	TF	TS468	-	095 (094.0)	+1	12.9	-	-	-	RNAV 1
7	TF	TS466	-	109 (108.0)	+1	12.0	-	-	-	RNAV 1
8	TF	TS464	-	126 (125.0)	+1	12.0	-	-	-	RNAV 1
9	TF	TS462	-	142 (140.5)	+1	9.9	-	@2150	-	RNAV 1
10	TF	BOMSU	-	239 (237.5)	+1	40.7	-	-1500 +790	-425	RNAV 1

TRN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TRN	-	-	+1	-	-	-	-	RNAV 1
2	TF	BITIS	-	072 (071.2)	+1	62.8	-	-	-	RNAV 1

2. RWY 25L/R - RNAV 1: SAPEN TWO JULIETT ARRIVAL (SAPEN 2J)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	SAPEN	-	-	+1	-	-	-	-	RNAV 1
2	TF	BUTGA	-	065 (063.5)	+1	67.0	-	+2150	-460	RNAV 1
3	TF	NUNGO	-	095 (094.0)	+1	12.2	-	@2150	-	RNAV 1
4	TF	TS468	-	095 (094.0)	+1	12.9	-	-	-	RNAV 1
5	TF	TS466	-	109 (108.0)	+1	12.0	-	-	-	RNAV 1
6	TF	TS464	-	126 (125.0)	+1	12.0	-	-	-	RNAV 1
7	TF	TS462	-	142 (140.5)	+1	9.9	-	@2150	-	RNAV 1
8	TF	BOMSU	-	239 (237.5)	+1	40.7	-	-1500 +790	-425	RNAV 1

3. RWY 25L/R - RNAV 1: VICAL THREE JULIETT ARRIVAL (VICAL 3J)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VICAL	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS484	-	336 (335.4)	+1	86.8	-	+4550	-	RNAV 1
3	TF	TS482	-	017 (016.0)	+1	23.2	-	+3650	-	RNAV 1
4	TF	BUTGA	-	049 (047.6)	+1	37.5	-	+2150	-460	RNAV 1
5	TF	NUNGO	-	095 (094.0)	+1	12.2	-	@2150	-	RNAV 1
6	TF	TS468	-	095 (094.0)	+1	12.9	-	-	-	RNAV 1
7	TF	TS466	-	109 (108.0)	+1	12.0	-	-	-	RNAV 1
8	TF	TS464	-	126 (125.0)	+1	12.0	-	-	-	RNAV 1
9	TF	TS462	-	142 (140.5)	+1	9.9	-	@2150	-	RNAV 1
10	TF	BOMSU	-	239 (237.5)	+1	40.7	-	-1500 +790	-425	RNAV 1

NIXIV TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	NIXIV	-	-	+1	-	-	-	-	RNAV 1
2	TF	VICAL	-	010 (008.7)	+1	84.3	-	-	-	RNAV 1

4. RNAV HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (s)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
BITIS	Y	029 (028.0)	+1	90	L	- FL200 +2450	-425	RNAV 1
BUTGA	Y	095 (094.0)	+1	60	L	-2450 +2150	-405	RNAV 1